



Light Weight

Perfect Performance

AVEEN E 15.625

Outdoor Fixed LED Display

AVEEN E 15.625

Outdoor Fixed LED Display



Light Weight PERFECT PERFORMANCE

Features

- A transparent outdoor fixed LED display, applies for exterior walls of buildings, landscapes, stadiums, etc.
- Super Light
- 6.8kg/panel, 18kg/m2, 80mm thick
- Front & Rear Installation and Maintenance options
- IP rating IP65, frame free for outdoor environment


Frame free and all-weather for outdoor environment

AVEEN E 15.625 is a transparent outdoor Pxed LED display, applies for exterior walls of buildings, landscapes, stadiums, bulletin boards & etc.




Super Light, Saving Cost

Aluminum profile, only 6.8kg/panel, 18kg/m2, 80mm thick, over 60% lighter and 50% thinner than the traditional product, lowering bearing requirement significant and making installation and uninstallation; 18% Penetration rate, good for reducing wind resistance and cooling the screen.



Traditional Panel



AVEEN E 15.625




Specifications:

eneral Specifications	AVEEN E 15.625
Model	E 15.625
LED Type	1R1G1B
Pixel Pitch (mm)	15.625
Panel Dimensions (WxHxD)/(mm)	250×1500×80
Pixel Per Panel	16×96
Panel Weight (kg)	6.8
Panel Material	Aluminum
Module Dimensions (LxWxH)/(mm)	18%
Brightness (nit)	7000
Color Contrast	4000:1
Refresh Rate (Hz)	2880
Gray scale (bit)	16
Color Temperature (K)	7500
Viewing Angle (H/V) (°)	120/60
Driving Type	Static
AC Operating Voltage (V)	100~240
Power Consumption (Max./Avg.)(W/m²)	450/150
Storage Temperature (°C)	- 40~ + 60
Operating Temperature (°C)	- 20~ + 50
Storage Humidity (RH)	10 % ~90 %
Operating Humidity (RH)	10 % ~90 %
IP Rating (Front/Rear)	IP65/IP65
LED Lifetime (H)	100000
Module Maintenance	Front/ Rear

Front & Rear Installation and Maintenance Available

Front & Rear installation and maintenance available, saving space; 6 in 1 sub-frame optional, makes installation simple



Sub-Frame

Head Quarters Contact:

Address : Keizersgracht 241, 1016 EA Amsterdam Tel # +31202612885 Email : info@aveenbv.com : sales@aveenbv.com : support@aveenbv.com

