



# Light Weight

**Perfect Performance** 

**AVEEN E 31.25** 

Outdoor Fixed LED Display

# **AVEEN E 31.25**

# **Outdoor Fixed LED Display**



Light Weight PERFECT PERFORMANCE

### **Features**

- A transparent outdoor fixed LED display, applies for exterior walls of buildings, landscapes, stadiums, etc.
- Super Light
- 16.6kg/sq.m
- Front & Rear Installation and Maintenance options
- IP rating IP65, frame free for outdoor environment

#### Reliable

High standard procedure, IP65 rating design, is suitable for outdoor usage. Frame and fan free reduce both installation and operation cost.





# Light

16.6kg/sq.m, over 65% lighter than traditional products. Easy to installation and disassembling.





## Permeable

45% permeability and low wind resistance, good for cooling and day lighting.





## **Specifications:**

#### **General Specifications AVEEN E E 31.25** E 31.25 Model 2R2G2B **LED Type** 31.25 Pixel Pitch (mm) 500×1000×100 Panel Dimensions (WxHxD)/(mm) 16×32 **Pixel Per Panel** Panel Weight (kg) 8.3 Aluminum ProÞle **Panel Material** 45% **Transparency Rate** 6000 **Brightness (nit) Color Contrast** 3400:1 4800 Refresh Rate (Hz) Gray scale (bit) 16 7500 Color Temperature (K) Viewing Angle (H/V) (°) 130/70 Static **Driving Type** 100~240 AC Operating Voltage (V) 130/70 Power Consumption (Max./Avg.)(W/m²) - 40~ + 60 Storage Temperature (°C) - 20~ + 50 **Operating Temperature (°C)** 10 % ~90 % Storage Humidity (RH) 10 % ~90 % **Operating Humidity (RH)** IP Rating (Front/Rear) IP65/IP65 100000 LED Lifetime (H) Front/ Rear **Module Maintenance**

#### Convenient

Easy to installation and maintenance, multiple secure designs ensure regular operation and safety.



Head Quarters Contact:

Address : Keizersgracht 241, 1016 EA Amsterdam Tel # +31202612885 Email : info@aveenbv.com : sales@aveenbv.com

: support@aveenbv.com

